

(12) UK Patent Application (19) GB (11) 2 360 423 (13) A

(43) Date of A Publication 19.09.2001

(21) Application No 0026358.2

(22) Date of Filing 27.10.2000

(30) Priority Data

(31) 11307805

(32) 28.10.1999

(33) JP

(71) Applicant(s)

NEC Corporation

(Incorporated in Japan)

7-1 Shiba 5-chome, Minato-ku, Tokyo 108-01, Japan

(72) Inventor(s)

Hidehiro Matsumoto

(74) Agent and/or Address for Service

Mathys & Squire

100 Grays Inn Road, LONDON, WC1X 8AL,
United Kingdom

(51) INT CL⁷

H04Q 7/24 // H04Q 7/22

(52) UK CL (Edition S)

H4L LRAA L205 L207

(56) Documents Cited

GB 2355563 A

(58) Field of Search

UK CL (Edition S) H4L LDGX LECCP LECCX LED LRAA
LRAB

INT CL⁷ H04L 12/66 29/06 , H04Q 7/22 7/24


ONLINE: WPI, PAJ, EPODOC, TXTUS0, TXTUS1,
TXTUS2, TXTUS3, TXTGB1, TXTEP1, TXTWO1

(54) Abstract Title

Mobile wireless communication system

(57) A wireless communication system includes a portable telephone 1, an information server 7, a plurality of gateway servers 5A, 5B, a switching apparatus 3 and a telephone server 8. The telephone which may be a WAP phone has a buffer memory for storing information received from the information server which may be an Internet server. The gateway servers have a buffer memory emulator 6 which stores data representing a specification of the buffer memory, and transmit data to the telephone based on the specification data. The switching apparatus 3 sets a connection between the telephone and the gateway servers. When a connection to a gateway server 5A becomes congested, the telephone may be connected to the server through a different access point. Alternatively, the telephone may be connected to a different gateway server 5B. A different gateway server 5B may be informed of the specification data in the previous servers memory emulator. The telephone server 8 informs the gateway servers of the telephones location.

Fig. 2



GB 2 360 423 A

Fig. 1 PRIOR ART




Fig. 2




Fig. 3

Tno	Sid	Cm
...		...

Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8





Fig. 9



MOBILE WIRELESS COMMUNICATION SYSTEM

Background of the Invention1. Field of the Invention

The present invention relates to a mobile communication system in which a portable terminal accesses
10 an information source server apparatus existing on a network through a wireless communication line. More particularly, the present invention relates to a mobile communication system, for reducing a time required for a portable terminal to access an information source server apparatus, a wireless
15 communication gateway server apparatus, a position information calculation system, and to a method for reducing a connection time in the system, and to a record medium for recording therein a connection time reduction program.

2. Description of the Related Art

20 Recently, a system has been proposed in which a portable terminal accesses information source server apparatus existing on a network (especially, the Internet) and obtains information from the network.

Fig. 1 shows an example of a configuration of a system
25 in which this portable terminal accesses the information source server apparatus existing on the network.

As shown in Fig. 1, a dedicated server apparatus

referred to as a wireless communication gateway server apparatus 24 is installed at an access point to a network, in order to access the network from a portable terminal 20.

5 This wireless communication gateway server apparatus 24 and the portable terminal 20 are connected to each other through a wireless communication line. In this wireless communication line, communication is performed, for example, by using a communication protocol referred to as WAP (Wireless Application Protocol) optimized for
10 the characteristic of a wireless communication and a portable terminal. Also, a communication between the wireless communication gateway server apparatus 24 and the information source server apparatus 26 on the network is
15 done in accordance with a standard protocol for the network [for example, in a case of the Internet, an Internet standard protocol {for example, HTTP (Hyper-Text Transfer Protocol) and TCP (Transmission Control Protocol)}].

 The wireless communication gateway server apparatus
20 24 has an executing device for executing: a process for carrying out a protocol conversion between a communication protocol on a wireless communication line and a standard protocol on a network on which the information source server apparatus 26 exists; a data conversion process, for
25 example, a process in which if information stored in the information source server apparatus 26 on the network is a document written under a HTML (Hypertext Markup Language)

type, this HTML-type document is converted into a document in a WML (Wireless Application Language) type used in the WAP; and a process in which if a document stored in information source server apparatus S on a network is, for example, a WML document in a text type, it is converted into a binary type, and then data is compressed.

Also, the wireless communication gateway server apparatus 24 has a buffer memory emulator 25, as shown in Fig. 1. In this apparatus, in order to solve the untableps in a communication condition caused by a bandwidth and a delay amount in a wireless data communication network and an intermission in a wireless communication line, this buffer memory emulator 25 transiently stores therein data sent by the information source server apparatus. The data for the buffer memory emulator 25 means, for example, a memory size and a consumed size of the buffer memory 2. The consumed size means, for example a size used for storing the information from the information source server apparatus 7. Then, it monitors a condition of a buffer memory at a portable terminal, carries out a control so that the data does not overflow the buffer memory, and sends the data to the portable terminal.

Moreover, the portable terminal can be freely moved. Thus, it is necessary that a current area in which the portable terminal itself presently exists is always reported to a system side (a switching station) (this

function is referred to as a position register).

The method for registering a position will be described below. An area number indicative of a position register area is always reported by a base station (not shown). The portable terminal 20 always compares an area number stored in the self-terminal with the reported area number, and sends a position register signal through the base station to a switching apparatus if those area numbers do not coincide with each other. The switching apparatus converts the position register signal sent by the portable terminal into position information on which a line setting can be performed, and then registers it in a position information database 23. Thus, the system side can recognize a new position of the portable terminal 20. Hence, for example, if this portable terminal is accessed, a switching apparatus 22 can send number information of the portable terminal to the position information database 23 and thereby connect a call to a desirable portable terminal, in accordance with information indicative of a position in which the portable terminal exists, from the number information fed back from the position information database 23.

The method for the portable terminal 20 to access the information source server apparatus 26 on the network will be described below, in the mobile communication system having the above-mentioned configuration. At first, when a power source of the portable terminal 20 is turned on,

position information of the portable terminal 20 is registered in the position information database 23 through the nearest base station. Next, since this portable terminal 20 issues a call to a telephone number of an access point which is registered in advance, a call is established between it and a wireless communication gateway server apparatus 24 having the access point.

An access request to the information source server apparatus 26 from the portable terminal 20 is reported to the wireless communication gateway server apparatus in a suitable wireless data protocol, for example, in the HTTP or WAP. So, it is possible to select and specify an information source server apparatus by using URL (Uniform Resource Locator).

However, in the above-mentioned conventional mobile communication system, when the portable terminal accesses the information source server apparatus existing on the network, it must telephone a registered telephone number of only one access point assigned to the portable terminal, and then access the network through this access point. Thus, if congestion is induced in this access point, a user of the portable terminal must wait to again telephone the access point. Also, it is impossible to obtain assurance that the user can access the network after an elapse of a predetermined time.

If the demand from the users becomes equal to or greater than the number of terminals (the congestion state)

that can be accommodated in the access point used when the wireless communication gateway server apparatus and the portable terminal communicate with each other, it is necessary to separately install the access point used by the portable terminal, in order to reduce a connection wait time of the user. At this time, a process for initializing a buffer memory within the wireless communication gateway server apparatus used just before must be initialized. Hence, the user must wait the time necessary for the initialization and a time for the connection to another access point.

If, because of the movement of the portable terminal or the occurrence of congestion in the access point, the establishment of the connection to the wireless communication gateway server apparatus used just before is disabled, the connection to the wireless communication gateway server apparatus is done through another access point. However, even in this case, it is necessary to initialize the process for monitoring the buffer memory. In this case, the user must further wait the switching time in the wireless communication gateway server apparatuses, in addition to the above-mentioned delay time. The fact that the user must wait not only results in a waste of a communication line resource, but also imposes an economic burden on the user when a communication fee or a service accounting based on time is charged.

The techniques with regard to the switched capacitor-

type digital-analog converter are disclosed in Japanese Laid Open Patent Application (JP-A-H7-264662), Japanese Laid Open Patent Application (JP-A-H9-130861), Japanese Laid Open Patent Application (JP-A-H10-210533), Japanese Laid Open Patent Application (JP-A-H10-327454) and Japanese Laid Open Patent Application (JP-A-H11-83976).

The present invention is intended to address the above-mentioned problems.

Summary of the invention

The present invention provides a mobile communication system which can reduce a time required for a portable terminal to access an information source server apparatus existing on a network, a wireless communication gateway server apparatus, and a position information calculation system, and also provides a method for reducing a connection time in the system, and a record medium for recording therein a connection time reduction program.

The mobile wireless communication system according to the invention is provided with information source server apparatus(7), a portable terminal(1), a plurality of wireless communication gateway server apparatuses(5A, 5B), a switching apparatus(3) and a wireless telephony server(8). The information source server apparatus stores information. The portable terminal carries out communication with the information source server apparatus and has a buffer memory(2) which stores the

information transmitted from the information source server apparatus. The plurality of wireless communication gateway server apparatuses, of which a specific one is
5 determined based on an informed position of the portable terminal, each have a buffer memory emulator which stores specification data which represents a specification of the buffer memory and transmits the information from the information source server apparatus
10 to the portable terminal based on the specification data. The switching apparatus sets a specific connection between the portable terminal and a specific wireless communication gateway server apparatus, or another connection between the portable terminal and another
15 wireless communication gateway server apparatus which is used when the communication between the portable terminal and the specific wireless communication gateway server apparatus congests. The wireless telephony server apparatus informs the position of the portable terminal
20 to the plurality of wireless communication gateway server apparatuses.

In another mobile wireless communication system according to the invention, the specific wireless communication gateway server apparatus (5A) requests the
25 switching apparatus to change a connection from the specific connection to the other connection based on the informed position.

In another mobile wireless communication system according to the invention, the specific wireless communication gateway server apparatus (5A) decides on the other wireless communication gateway server apparatus (5B) so that a new connecting destination of a connection between the one connection and the other connection is determined.

In another mobile wireless communication system according to the invention, the specific wireless communication gateway server apparatus (5A) informs the other wireless communication gateway server apparatus of the specification data which is read from the buffer memory emulator. Furthermore, the other wireless communication gateway server apparatus (5A) stores the read specification data in the buffer memory emulator thereof and transfers the information from the information source server apparatus to the portable terminal based on the read specification data.

Another mobile wireless communication system is provided with a network which is connected to the specific wireless communication gateway server apparatus, the another wireless communication gateway server apparatus, the switching apparatus, and the wireless telephony server apparatus. In the above mobile wireless communication system, the specific wireless communication gateway server apparatus, the another wireless communication gateway server apparatus, the switching apparatus, and the

wireless telephony server apparatus communicate through the network.

Another mobile wireless communication system is provided with an internet network which is connected to the specific wireless communication gateway server apparatus, the another wireless communication gateway server apparatus, the switching apparatus, and the wireless telephony server apparatus. In the above mobile wireless communication system, the specific wireless communication gateway server apparatus, the another wireless communication gateway server apparatus, the switching apparatus and the wireless telephony server apparatus communicate through the internet network.

Another mobile wireless communication system is provided with a satellite network which is connected to the specific wireless communication gateway server apparatus, the another wireless communication gateway server apparatus, the switching apparatus, and the wireless telephony server apparatus. In the above mobile wireless communication system, the specific wireless communication gateway server apparatus, the another wireless communication gateway server apparatus, the switching apparatus, and the wireless telephony server apparatus communicate through the satellite network.

The mobile wireless communication system according to the invention is provided with an information source server apparatus (7), a portable terminal (1), a wireless

communication gateway server apparatus (5A), a switching apparatus (3), a wireless telephony server apparatus (8). The information source server apparatus stores information. The portable terminal carries out a communication with the information source server apparatus and has a buffer memory which stores the information transmitted from the information source server apparatus. The wireless communication gateway server apparatus has a buffer memory emulator which stores specification data which represents a specification of the buffer memory. Furthermore, the wireless communication gateway server apparatus has a plurality of access points (APa, APb), a specific one of which is determined based on an informed position of the portable terminal. Furthermore, the wireless communication gateway server apparatus transfers the information from the information source server apparatus to the portable terminal based on the specification data. The switching apparatus sets a specific connection between the portable terminal and a specific access point or another connection between the portable terminal and another access point, which is used when the one access point congests. The wireless telephony server apparatus informs the position of the portable terminal to the wireless communication gateway server apparatus.

In another mobile wireless communication system, the wireless communication gateway server apparatus requests the switching apparatus to change a connection from the

apparatus. In the requesting, a change from a specific connection to the other connection is requested to a switching apparatus, which sets a connection for the portable terminal based on the informed position.

5 Another method for mobile wireless communication involves a step of communicating. In the communicating, the specific wireless communication gateway server apparatus, the another wireless communication gateway server apparatus, the switching apparatus and the wireless
10 telephony server apparatus communicate through a network.

In another method for mobile wireless communication, the specific wireless communication gateway server apparatus, the another wireless communication gateway server apparatus, the
15 switching apparatus and the wireless telephony server apparatus communicate through an internet network.

In another method for mobile wireless communication, the specific wireless communication gateway
20 server apparatus, the another wireless communication gateway server apparatus, the switching apparatus and the wireless telephony server apparatus communicate through a satellite network.

In another method for mobile wireless communication,
25 a specific connection between the portable terminal and one access point of a wireless communication gateway server apparatus is changed to another connection

between the portable terminal and another access point of the wireless communication gateway server apparatus, which is used when the wireless communication gateway server apparatus has congestion.

5 The above method of mobile wireless communication involves steps of informing and requesting. In the informing, a position of the portable terminal from a wireless telephony server apparatus is informed to the wireless communication gateway server apparatus. In the
10 requesting, a change from a specific connection to the other connection is requested to a switching apparatus which sets a connection for the portable terminal based on the informed position.

 In the above method for mobile wireless
15 communication, the wireless communication gateway server apparatus, the switching apparatus and the wireless telephony server apparatus communicate through a network.

 In the above method for mobile wireless
20 communication, the wireless communication gateway server apparatus, the switching apparatus and the wireless telephony server apparatus communicate through an internet network.

 In the above method for mobile wireless
25 communication, the wireless communication gateway server apparatus, the switching apparatus and the wireless telephony server apparatus communicate through a

satellite network.

The wireless communication gateway server apparatus according to the invention is provided with a buffer memory emulator. The buffer memory emulator stores
5 specification data which represents a specification of a buffer memory of a portable terminal. In the above wireless communication gateway server apparatus, specific connection with the portable terminal is changed to another connection between the portable terminal and
10 another wireless communication gateway server apparatus, which is used when congestion of the specific connection happens. In the above wireless communication gateway server apparatus the specification data in the buffer memory is transferred to the another
15 wireless communication gateway server apparatus.

In the above wireless communication gateway server apparatus, a change is requested to the switching apparatus which sets a connection for the portable terminal from the specific connection to the other connection based on
20 position data of the portable terminal.

The above wireless communication gateway server apparatus is provided with a plurality of access points, wherein a specific one of the plurality of access points is determined based on an informed position of the
25 portable terminal.

In the above wireless communication gateway server apparatus, a change is requested to the switching apparatus

which sets a connection for the portable terminal from a specific one connection of the specific one access point to another connection of another access point based on the position of the portable terminal.

- 5 A further broad aspect of the invention is as set out in claim 1.

Brief Description of the Drawings

Preferred features of the present invention will now be described, by way of example only, with reference to the accompanying drawings, in which:-

10

Fig. 1 is a block diagram showing a configuration of a conventional mobile wireless communication system;

Fig. 2 is a block diagram showing a configuration of an embodiment according to the present invention;

Fig. 3 is a view showing a management table;

15

Fig. 4 is a view showing a configuration of an embodiment;

Fig. 5 is a view of a first communication example involving a connection to an access point managed by the same wireless communication gateway server apparatus;

20

Fig. 6 is a view of a second communication example involving a connection to an access point managed by the same wireless communication gateway server apparatus;

Fig. 7 is a view of a first communication example involving a connection to an access point managed by a different wireless communication gateway server apparatus;

25

Fig. 8 is a view of a second communication example involving a connection to an access point managed by a different wireless communication gateway server apparatus; and,

Fig. 9 is a block diagram showing a configuration of another embodiment.

Description of the Preferred Embodiments

5 The embodiments with regard to a mobile communication system, a wireless communication gateway server apparatus, a position information calculation system, a method for reducing a connection time in the system and a record medium for recording therein a
10 connection time reduction program, according to the present invention, will be described below in detail with reference to the attached drawings.

Fig. 2 shows the configuration of the embodiment according to the present invention. The embodiment
15 according to the record medium for recording therein the connection time reduction program can be attained by storing a record medium, which records therein a control program, in the following respective devices. As this record medium, a semiconductor memory, an optical disc,
20 a magneto-optic disc, a magnetic record medium and the like can be used.

As shown in Fig. 2, this embodiment is provided with: a portable terminal 1 which uses a wireless communication line; a switching apparatus 3 for carrying out the
25 desirable connection, based on a telephone number of a destination included in a call connection information from the portable terminal 1 and the like; a position

information database 4 for recording therein a current position of the portable terminal 1; a wireless communication gateway server apparatus 5 which exists on a network and communicates through the wireless communication line with the portable terminal 1; information source server apparatus 7 that exists on the network on which the wireless communication gateway server apparatus 5 exists; and a wireless telephony server apparatus 8 that exists on the network and can obtain a position information of the portable terminal 1 from the position information database 4. In this embodiment, between a plurality of wireless communication gateway server apparatuses 5, each of the wireless communication gateway server apparatuses 5, the information source server apparatus 7 and the wireless telephony server apparatus 8 are connected through the Internet to each other, and they can send and receive information to and from each other. However, this network is not limited to the Internet.

The portable terminal 1 is constituted by a terminal which carries out a communication by using a wireless communication line such as PHS (Personal Handy-phone System), a portable telephone and the like. Also, the portable terminal 1 has a buffer memory 2 for storing therein information transferred by the information source server apparatus 7 and the like. The information means, for example HTML (Hypertext Markup Language) data for a web

site.

In order that a system side (a switching apparatus side) recognizes a position of the movable portable terminal 1, the position information database 4 captures
5 an identifier and a position of a base station belonging to a cell on a control route 10 in the wireless communication line, in a case of a cell type, and always registers therein the newest position of the portable terminal 1. Actually, a base station (not shown) always transmits a position
10 information of the base station within the cell. The portable terminal 1 stores therein the position information transmitted by the nearest base station. When because of a movement of a user, the portable terminal 1 is moved from a cell managed by the base station to another
15 cell, if a position information received at that location is different from the stored position information, the stored position information is changed into the newly received position information, and a register request with regard to the change into a new position is performed on
20 the base station. This position information is registered in the position information database 4 through a common line signal network from the switching apparatus 3.

The switching apparatus 3 switches a connection to
25 a line for a destination indicated by a telephone number, in accordance with the telephone number included in the connection request from a wireless communication gateway

server apparatus, or a portable terminal.

The position information database 4 has a function of searching the stored position information of the portable terminal, in accordance with an individual number of a portable terminal transferred by the wireless telephony server apparatus 8, and finding out a cell ID indicative of a cell to which the portable terminal currently belongs, and then transmitting to a request source. Especially, in a case of a PDC (Personal Digital Cellular phone) type, this position information database 4 is referred to as HLR (Home Location Register).

Fig. 3 shows an example of a management table managed by the position information database. As shown in Fig. 3, the management table managed by the position information database records therein a terminal number of each portable terminal, a cell ID indicative of a position of a base station to which the portable terminal currently belongs, an accounting meter for calculating a usage fee for each portable terminal and the like.

The wireless communication gateway server apparatus 5 has a buffer memory emulator 6. This buffer memory emulator 6, in order to solve the unstableness of a communication condition caused by a network, a band width and a delay amount of the wireless communication line network, and an intermission of the wireless communication line, transiently accumulates therein a data transmitted by the information source server apparatus 7, and monitors

a condition of the buffer memory 2 which is mounted in the portable terminal 1 and stores therein the data, and carries out a control so that the data does not overflow the buffer memory 2, and then sends the data to the portable
5 terminal 1.

Also, the wireless communication gateway server apparatus 5 has the following functions in addition to the above-mentioned function. For example, it has: a function in which if the WAP is used for a communication
10 protocol in the portable terminal 1 using the wireless communication line and then a standard protocol in the Internet is used for a communication protocol in the network, a protocol conversion is done between the communication protocol in the WAP and the standard protocol
15 in the network; a data conversion function, for example, a function in which if a document in the HTML type is stored in the information source server apparatus 7 on the network, the document in the HTML type is converted into a document in the WML (Wireless Markup Language) type used in the WAP,
20 a function in which if a document in the text type is stored in the information source server apparatus 7 on the network, the document in the text type is converted into the binary type, and the data is compressed; and the like.

The information source server apparatus 7, which
25 exists on the network, transmits the stored information, in accordance with a request from the portable terminal 1.

The wireless telephony server apparatus 8 is a kind of information source server apparatus for providing information. So, it can use the position information database 4 to thereby obtain information with regard to the portable terminal 1 registered in the position information database 4.

A first object of a first embodiment having the above-mentioned configuration lies in a reduction of a time necessary for a connection process to the Internet of users by establishing another access point if the demand from the users becomes equal to or greater than the number of terminals that can be accommodated in an access point (a congestion state), in the access point serving as a connection point to the Internet, when the portable terminal 1 accesses information source server apparatus 7 connected to the Internet.

A second object of the embodiment having the above-mentioned configuration lies in a reduction of a time necessary for a re-connection by preparing in advance the condition of a buffer memory before a disconnection with regard to the portable terminal 1, in the wireless communication gateway server apparatus 5, on the basis of a connected position, if a congestion is induced in an access point connected just before, when the portable terminal 1 again accesses information source server apparatus, at a time of the disconnection of the wireless communication line or after a user ends a communication.

In order to attain the first object, the wireless communication gateway server apparatus 5, if a congestion is induced in an access point managed by it, instructs the switching apparatus 3 to carry out a connection to another
5 access point. Then, the switching apparatus 3 carries out a process for carrying out a connection to the instructed access point, if the portable terminal 1 issues a call to the access point in which the congestion is induced.

Accordingly, it is possible to solve the trouble
10 induced when the conventional portable terminal accesses the network, and the trouble in which since the number of access points is one, if the congestion is induced in the access point, it must issue a call to the access point again after a while or the connection can not be established even
15 if it tries to issue a large number of calls to the access point.

In order to attain the second object, the wireless communication gateway server apparatus 5 for transiently storing in a buffer memory (not shown) information
20 transferred by the information source server apparatus 7 and a position and an attribute value of a portable terminal connected to an access point, stores therein the above-mentioned information initialized at the stage when the communication with the portable terminal is
25 disconnected, without the initialization for a certain period. Also, the wireless communication gateway server apparatus 5 recognizes the histories with regard to an

individual number of a portable terminal that is connected to the wireless telephony server apparatus 8 for a certain period and also connected to an access point which it belongs, and information about a cell ID in which the portable terminal exists. This can be attained by the following operations. That is, the wireless communication gateway server apparatus 5 transfers the kind report sent by the portable terminal to the wireless telephony server apparatus 8 for each certain cycle. The wireless telephony server apparatus 8 transfers the sent kind report to the position information database 4. Then, it obtains a cell ID indicative of a cell to which the portable terminal 1 currently belongs, and then transfers to the wireless communication gateway server apparatus 5. By the way, the kind report transferred to the wireless communication gateway server apparatus 5 from the portable terminal 1 at the time of the connection to the access point includes the terminal attribute indicative of an individual number of the portable terminal, an amount of the buffer memory, a size of a display region, a processing ability and the like.

Thus, after the wireless communication line is disconnected or after the user of the portable terminal 1 ends the communication, when the portable terminal again accesses the information source server apparatus 7, if a congestion is induced in an access point and thereby the portable terminal is connected to another access point,

since the wireless communication gateway server apparatus
5 stores therein the information transferred by the
information source server apparatus 7 and the position and
the attribute value of the portable terminal connected to
5 the access point, it is possible to continue the process
in the buffer memory emulator 6 and also possible to
continue the services such as the accounting process and
the like.

Even if the movement of the user of the portable
10 terminal 1 causes the portable terminal 1 to be connected
to another access point different from an access point
connected just before and further the access point is a
wireless communication gateway server apparatus different
from a wireless communication gateway server apparatus
15 carrying out a process just before, the wireless
communication gateway server apparatus sends a kind report
of the portable terminal to the wireless telephony server
apparatus 8. The wireless telephony server apparatus 8
obtains the position information before and after the
20 connection to the portable terminal from the position
information database 4, and compares them with each other,
and then finds out the wireless communication gateway
server apparatus used just before. Thus, various
parameters for the buffer memory emulator can be obtained
25 from the wireless communication gateway server apparatus
connected just before. Hence, it is possible to reduce
the time necessary for the connection process and also

possible to continue the services such as the accounting process and the like. By the way, the various parameters for the buffer memory emulator 6 include a parameter indicative of a condition of the buffer memory, a parameter
5 indicative of an attribute of a portable terminal, a parameter indicative of a position information of the portable terminal and the like.

A series of flows in the above-mentioned processes according to this embodiment will be described below in
10 detail.

As shown in Fig. 2, the portable terminal 1 captures the identifier and the position of the base station belonging to the cell on the control route 10 in the wireless communication line, in the case of the cell type, and always
15 registers the newest position in the position information database 4. Also, the portable terminal 1 is connected to the wireless communication gateway server apparatus 5 through the wireless communication network up to the access point. The connection to the wireless communication
20 gateway server apparatus 5 from the portable terminal 1 is established by issuing a call to a telephone number of the access point assigned to the portable terminal. After that, the communication route to the wireless communication gateway server apparatus is established
25 through a proper wireless communication protocol, for example, the HTTP or the WAP, as shown in Fig. 4.

The portable terminal 1, when it is connected to the

wireless communication gateway server apparatus 5,
transfers the kind report to identify the portable terminal,
to the wireless communication gateway server apparatus 5.
This kind report includes the terminal attribute, such as
5 the individual number of the portable terminal, the amount
of the buffer memory, the size of the display region, the
processing ability and the like.

The wireless communication gateway server apparatus
5 validates the legality of the portable terminal, in
10 accordance with the kind report obtained from the portable
terminal 1. In this process, the wireless communication
gateway server apparatus firstly transfers the kind report
sent by the portable terminal to the wireless telephony
server apparatus. The wireless telephony server
15 apparatus transfers the individual number of the portable
terminal from the transferred kind report to the position
information database, and obtains the kind report of the
portable terminal registered in the position information
database. Then, the legality of the portable terminal is
20 validated by comparing those kind reports with each other.

The portable terminal can select and specify
information source server 7 by specifying URL (Uniform
Resource Locator) of information source server apparatus
7 on a network from which a user desires to obtain
25 information.

The wireless communication gateway server apparatus
5, when the legality of the portable terminal is proved,

converts the wireless communication protocol used in the communication with the portable terminal into a standard protocol in the Internet, for example, a communication protocol based on the HTTP or the TCP, and then communicates
5 with the information source server apparatus 7 requested by the portable terminal 1. Thus, the wireless communication gateway server apparatus 5 can obtain the information stored in the information source server apparatus 7. The wireless communication gateway server
10 apparatus 5 stores the information sent by the information source server apparatus 7 in a buffer memory (not shown).

At this time, in the wireless communication gateway server apparatus 5, in order to monitor the overflow of the buffer memory 2 on the terminal side, the buffer memory
15 emulator 6 calculates a consumptive amount of the buffer memory based on the number of data packets received by the portable terminal 1 and the number of already processed packets.

Here, let us suppose that a congestion is induced
20 in the access point, when the portable terminal again accesses the information source server apparatus 7, after the wireless communication line is disconnected or after a user ends the communication. The wireless telephony server apparatus 8, when the congestion is induced in the
25 access point to which it belongs, instructs the switching apparatus 3 to carry out the connection to another access point. Then, the switching apparatus 3, when the portable

terminal 1 issues a call to the access point in which the congestion is induced, carries out a process for switching a connection to the instructed access point.

At this time, when the portable terminal issues the
5 call, the connection to the access point is done. However, there are the case that it is connected to an access point belonging to the same wireless communication gateway server apparatus, as shown in Fig. 5 or 6, and the case that it is connected to an access point belonging to a
10 different wireless communication gateway server apparatus because of the movement of the portable terminal, as shown in Fig. 7 or 8.

At first, with reference to Figs. 4 and 5, a communication example is described in which a congestion
15 is induced in an illustrated access point A, and it is connected to an access point B belonging to the same wireless communication gateway server apparatus 5A at a time of a re-connection. For the purpose of simple explanation, it is assumed that the access points A, B
20 belong to the same cell.

The wireless communication gateway server apparatus 5A, when it is connected to the portable terminal 1, compares a kind report reported by the portable terminal 1 with a kind report of the portable terminal 1, which is
25 stored in advance in the buffer memory. Then, it is checked whether or not the portable terminal 1 requesting the connection is the same portable terminal. If it is

checked that the reported kind report is identical to the kind report stored in the buffer memory, the buffer memory emulator 6 does not carry out the process for initializing information with regard to the portable terminal.

5 Thus, it is possible to reduce the time necessary for the process for connecting the portable terminal, and also possible to continue the services such as the accounting process and the like. Hence, when the communication fee or the service accounting based on the
10 time is charged, it is possible to reduce the economic burden on the user.

 In order to validate whether or not the legality of the portable terminal and the accounting process based on the provision service are started, the kind report of the
15 portable terminal 1 at the time of the re-connection is sent through the Internet to the wireless telephony server apparatus 8. The wireless telephony server apparatus 8 sends the individual number of the portable terminal 1 included in the received kind report to the position
20 information database 4, and obtains an attribute value registered in the position information database 4. This attribute value is compared with the attribute value obtained from the wireless communication gateway server apparatus 5A to thereby check the legality of the portable
25 terminal. Moreover, an accounting condition of the portable terminal 1 is checked by obtaining an accounting condition registered in the position information database

4. After the check, the wireless telephony server apparatus 8 sends a check report to the wireless communication gateway server apparatus 5 sending the kind report. Accordingly, the process of the buffer memory emulator 6 is continued.

By the way, the wireless communication gateway server apparatus 5A checks a terminal which is connected to the wireless telephony server apparatus 8 at a certain cycle and connected to the access point that it belongs.

10 After the check, the wireless telephony server apparatus 8 sends a check report to the wireless communication gateway server apparatus 5A sending the kind report. Accordingly, the process of the buffer memory emulator 6 is continued.

15 Usually, the time necessary for the initializing process is longer than that of the checking process, because of the re-establishment of the configuration of the buffer memory. Thus, the connection time in this method is shorter than that of the conventional technique.
20 Hence, the continuation of the process in the buffer memory emulator enables the services, such as the accounting process and the like, to be continued.

A case will be described below in which the portable terminal 1 is moved from a cell A to another cell B and
25 it is connected to an access point C belonging to a different wireless communication gateway server apparatus 5B.

When the portable terminal 1 is connected to the same

wireless communication gateway server apparatus at the time of the re-connection to the mobile communication system, a kind report of the portable terminal just before coincides with a kind report stored in the buffer memory emulator. However, if it is connected to a different wireless communication gateway server apparatus, the kind report reported by the portable terminal 1 does not coincide with a kind report of the portable terminal that is stored in the wireless communication gateway server apparatus.

So, the wireless communication gateway server apparatus sends the reported kind report of the portable terminal through the Internet to the wireless telephony server apparatus 8.

The wireless telephony server apparatus 8 accesses the position information database 4, and finds out a URL of the wireless communication gateway server apparatus 5A to which the portable terminal 1 requesting the connection is connected just before. Then, the found out URL of the wireless communication gateway server apparatus 5A is transferred to the wireless communication gateway server apparatus 5B sending the kind report.

The wireless communication gateway server apparatus 5B to which the URL is reported requests various parameters held by the buffer memory emulator, to the wireless communication gateway server apparatus 5B of the reported URL. The requested wireless communication gateway server

apparatus 5A sends the various parameters held by the buffer memory emulator, to the wireless communication gateway server apparatus 5A of the request source. The wireless communication gateway server apparatus 5B
5 receiving the report of the various parameters with regard to the portable terminal 1 copies the received various parameters of the portable terminal 1 to the buffer memory emulator.

At this time, the portable terminal 1 is acquired
10 by the wireless telephony server apparatus 8, and the wireless telephony server apparatus 8 is cyclically connected to the wireless communication gateway server apparatuses 5A, 5B. Thus, it is possible to judge the terminal connected to the access point under the control
15 of each wireless communication gateway server apparatus. Hence, as compared with the case that the portable terminal moved to another cell is initialized by the wireless communication gateway server apparatus, in this method, the process in the buffer memory emulator can be continued
20 to thereby continue the services including the accounting process and the like. This results in the reduction in the time necessary for the connection process.

By the way, the above-mentioned embodiments, the HLR is used as the position information of the portable
25 terminal. However, the position information of the portable terminal may be grasped by using a geodetic satellite system and the like.

In this case, as shown in Fig. 9, receivers for receiving an electric wave from a satellite 13 are mounted on a portable terminal side 1 and a ground station 12. The GPS ground station 12 can receive all electric waves from all satellites. However, a GPS receiver 11 of a portable terminal can not receive the electric waves from all the satellites. So, a satellite from which the GPS receiver 11 of this portable terminal can receive the electric wave is reported to the GPS ground station 12. Accordingly, the GPS ground station 12 can find out a position of the portable terminal from a position of the satellite from which this electric wave can be received. This position information is used by the wireless telephony server apparatus.

15 In the above-mentioned embodiments, the wireless communication gateway server apparatus and the wireless telephony server apparatus are connected to each other through the Internet. However, a private line may be used in order to make the secret degree higher.

20 The above-mentioned embodiments do not depend on a particular wireless communication protocol. Thus, at a time of an internationally mutual connection including a foreign country, if it is possible to exchange a position information or it is possible to exchange a transmission reception type for the various parameters of the buffer memory emulator and the terminal kind report, the application does not need to be limited to a particular

territory.

Also, the similar effect can be attained even if the wireless communication gateway server apparatus also has the function of the wireless telephony server apparatus.

5 Moreover, in the above-mentioned embodiments, the access point is connected to specific one wireless communication gateway server apparatus. However, even if associated with the movement of the portable terminal, the access point automatically selects the nearest wireless
10 communication gateway server apparatus, it is possible to apply the process similar to that of the connection to the above-mentioned different wireless communication gateway server apparatus, and it is possible to attain the similar effect.

15 Advantageous Effects of the Invention

As can be evident from the above-mentioned explanations, in the mobile communication system, the method for reducing the connection time and the record medium for recording therein the program, the wireless
20 communication gateway server apparatus, if a congestion is induced in an access point that is used as a connection point to a wireless communication line and managed by the wireless communication gateway server apparatus, instructs the switching apparatus to carry out the
25 connection to another access point. Thus, even if the congestion is induced in the access point, it is possible to establish another access point in which the congestion

is not induced. Hence, it is possible to reduce the time necessary for the connection of the portable terminal.

The wireless communication gateway server apparatus holds therein the information with regard to the portable terminal connected to the access point managed by the wireless communication gateway server apparatus and the information, which is transferred by the information source server apparatus and stored in the memory, for the predetermined period even after the end of the communication with the portable terminal. When the congestion is induced in the managed access point, it compares the information with regard to the portable terminal, which is sent by the portable terminal connected to another access point, with the information with regard to the portable terminal previously connected to the access point to which it belongs. If their information coincide with each other, the information with regard to the portable terminal connected to the access point and the information stored in the memory are used to then resume the communication with the portable terminal. Thus, it is possible to reduce the time required when the portable terminal tries the process for carrying out the connection to the network. Hence, if the communication fee and the service based on the time are charged, it is possible to reduce the economic burden on the user.

The wireless communication gateway server apparatus transfers the information with regard to the portable

terminal connected to the access point managed by it to the wireless telephony server apparatus, and the wireless telephony server apparatus transfers the transferred information with regard to the portable terminal to the position information memory. Then, it is validated whether or not the position of the portable terminal is moved. If the portable terminal is moved, an address information on the network of the wireless communication gateway server apparatus connected before the movement is calculated from the position information. Thus, in the re-communication with the portable terminal whose the connection is once disconnected, the condition of the buffer memory can be prepared in advance in the wireless communication gateway server apparatus corresponding to the position to which the portable terminal is connected. Hence, it is possible to reduce the time in the connection processing time.

The wireless communication gateway server apparatus transfers the information with regard to the portable terminal connected to the access point managed it to the wireless telephony server apparatus, and the wireless telephony server apparatus transfers the information with regard to the portable terminal, which is reported by the portable terminal, to the position information memory, and it obtains the information with regard to the portable terminal, which is stored in the position information memory. The obtained information is compared with the

information with regard to the portable terminal, which is reported by the wireless communication gate, to then validate the legality of the portable terminal. Thus, it is possible to protect an illegal portable terminal from
5 accessing the network.

The wireless communication gateway server apparatus transfers the information with regard to the portable terminal connected to the access point managed by it to the wireless telephony server apparatus, and the wireless
10 telephony server apparatus transfers the transferred information with regard to the portable terminal to the position information memory. So, the accounting condition of the portable terminal can be checked by checking the accounting condition of the portable terminal
15 from the position information memory. When the access to the network is again tried, the accounting process can be continued.

The wireless communication gateway server apparatus grasps the histories of the information with regard to the
20 portable terminal that is connected to the wireless telephony server apparatus in the certain cycle and connected to the access point to which it belongs, and the position information of the portable terminal. Thus, it is possible to judge the terminal connected to the access
25 point under the control of the wireless communication gateway server apparatus.

The wireless communication gateway server apparatus

of the present invention instructs the switching apparatus, which carries out a connection to a line specified by a destination equipment number included in a call if a congestion is induced in the access point that is managed
5 by the wireless communication gateway server apparatus and used as a connection point to the wireless communication line, to carry out the connection to another access point, when a connection to an access point is requested by an equipment using the wireless communication line. Thus,
10 it is possible to establish another access point in which the congestion is not induced even if the congestion is induced in the access point. Hence, it is possible to reduce the time necessary for the connection to the network of the equipment using the wireless communication line.

15 The wireless communication gateway server apparatus holds therein information with regard to an equipment connected to the access point managed by the wireless communication gateway server apparatus and information transferred from an equipment existing on the network, for
20 a predetermined period even after the end of the communication with the equipment using the wireless communication line. Then, when a congestion is induced in the access point managed by it, it compares the information with regard to the equipment, which is sent
25 by the equipment using the wireless communication line and connected to another access point, with information with regard to an equipment using a wireless communication line

previously connected to the access point to which it belongs. If their information coincide with each other, the information with regard to the equipment connected to the access point and the stored information are used to
5 then resume the communication with the equipment using the wireless communication line. Thus, it is possible to reduce the time required when the equipment using the wireless communication line tries the process for carrying out the connection to the network. Hence, when the
10 communication fee and the service based on the time are charged, it is possible to reduce the economical burden on the user.

In the position information calculation system of the present invention, the wireless telephony server
15 apparatus transfers information with regard to an equipment using a wireless communication line to the position information memory. Then, it is validated whether or not a position of the equipment is moved. If it is moved, an address information of a managing device
20 for managing an access point to which the equipment using the wireless communication line is connected before the movement is calculated from the position information. For example, the calculated address information is transferred to the managing device for managing the access
25 point. Thus, in a re-communication with the equipment using the wireless communication line whose connection is once disconnected, the information with regard to the

equipment using the wireless communication line can be prepared in advance in the managing device corresponding to the position to which this equipment is connected. Hence, it is possible to reduce the connection processing
5 time.

The wireless telephony server apparatus transfers identification information of the equipment that is included in the information with regard to the equipment that is reported by the equipment using the wireless communication line, to the position information memory, and
10 it obtains information with regard to the equipment that is stored in the position information memory. The obtained information is compared with information with regard to the equipment that is reported by a wireless
15 communication gate. The legality of the equipment using the wireless communication line can be validated to thereby prevent illegal equipment from accessing the network.

While the present invention has been described in
20 its preferred embodiments, it is to be understood that the words which have been used are words of description rather than limitation, and that changes may be made to the invention without departing from its scope as defined by the appended claims.

25 Each feature disclosed in this specification (which term includes the claims) and/or shown in the drawings may be incorporated in the invention independently of other disclosed and/or illustrated features.

The text of the abstract filed herewith is repeated here as part of the specification.

A mobile wireless communication system includes a portable terminal, a plurality of wireless-communication gateway server apparatuses, a switching apparatus, and a wireless telephony server apparatus. An information source server apparatus stores information. The portable terminal carries out communication with the information source server apparatus through a wireless communication line, and has a buffer memory which stores the information from the information source server apparatus. The plurality of wireless communication gateway server apparatuses have a buffer memory emulator which stores specification data. The specification data represents a specification of the buffer memory. Furthermore, the plurality of wireless communication gateway server apparatuses transmit the information to the portable terminal based on the specification data. The switching apparatus sets a connection between the portable terminal and specific wireless communication gateway server apparatus, or another connection between the portable terminal and the other wireless communication gateway server apparatus, which is used when the specific wireless communication gateway server apparatus has congestion. The wireless telephony server apparatus informs a position of the portable terminal to the specific wireless communication gateway server apparatus.

CLAIMS:

1. A mobile wireless communication system comprising:
an information source server apparatus storing
information;

a portable terminal carrying out communication with
the information source server apparatus and having a
buffer memory which stores the information transmitted
from the information source server apparatus;

wireless communication gateway server means having
buffer memory emulator means which stores specification
data representing a specification of the buffer memory and
transfers the information from the information source
server apparatus to the portable terminal based on the
specification data;

a switching apparatus setting first and second
connections between the portable terminal and respective
first and second points on the wireless communication
gateway server means, the second connection being used
when the first connection congests; and,

a wireless telephony server apparatus informing the
position of the portable terminal to the wireless communi-
cation gateway server means.

2. A mobile wireless communication system comprising:
an information source server apparatus storing
information;

a portable terminal carrying out communication with

the information source server apparatus through a wireless communication line and having a buffer memory which stores the information transmitted from the information source server apparatus;

a plurality of wireless communication gateway server apparatuses, wherein a specific one of the plurality of wireless communication gateway server apparatuses, which specific one is determined based on an informed position of the portable terminal, has a buffer memory emulator which stores specification data which represents a specification of the buffer memory and transmits the information from the information source server apparatus to the portable terminal based on the specification data;

a switching apparatus setting a specific connection between the portable terminal and a specific wireless communication gateway server apparatus or another connection between the portable terminal and another wireless communication gateway server apparatus, the other connection being used when the communication between the portable terminal and the specific wireless communication gateway server apparatus congests; and,

a wireless telephony server apparatus informing the position of the portable terminal to the plurality of wireless communication gateway server apparatuses.

3. A mobile wireless communication system as claimed in claim 2,

wherein the specific wireless communication gateway server apparatus requests the switching apparatus to change a connection from the specific connection to the other connection based on the informed position.

4. A mobile wireless communication system as claimed in claim 2,

wherein the specific wireless communication gateway server apparatus decides on the other wireless communication gateway server apparatus, so that a new connecting destination of a connection between the one connection and the other connection is determined.

5. A mobile wireless communication system as claimed in claim 2,

wherein the specific wireless communication gateway server apparatus informs the other wireless communication gateway server apparatus of the specification data which is read from the buffer memory emulator, and

the other wireless communication gateway server apparatus stores the read specification data in the buffer memory emulator thereof and transfers the information from the information source server apparatus to the portable terminal based on the read specification data.

6. A mobile wireless communication system comprising:
an information source server apparatus storing information;

a portable terminal carrying out communication with the information source server apparatus and having a buffer memory which stores the information transmitted from the information source server apparatus;

a wireless communication gateway server apparatus having a buffer memory emulator which stores specification data which represents a specification of the buffer memory and having a plurality of access points, a specific one of which is determined based on an informed position of the portable terminal, and transfers the information from the information source server apparatus to the portable terminal based on the specification data;

a switching apparatus setting a specific connection between the portable terminal and a specific access point or setting another connection between the portable terminal and another access point, the other connection being used when the one access point congests; and,

a wireless telephony server apparatus informing the position of the portable terminal to the wireless communication gateway server apparatus.

7. A mobile wireless communication system as claimed in claim 6,

wherein the wireless communication gateway server apparatus requests the switching apparatus to change a connection from the specific connection to the other connection based on the informed position.

8. A mobile wireless communication system as claimed in claim 6,

wherein the wireless communication gateway server apparatus refers to the specification data in the buffer memory emulator to access the portable terminal through the other access point.

9. A mobile wireless communication system as claimed in claim 2 or 6, comprising:

a network which is connected to the wireless communication gateway server apparatus, the switching apparatus, and the wireless telephony server apparatus,

wherein the wireless communication gateway server apparatus, the switching apparatus, and the wireless telephony server apparatus communicate through the network.

10. A mobile wireless communication system as claimed in claim 2 or 6, comprising:

an internet network which is connected to the wireless communication gateway server apparatus, the switching apparatus, and the wireless telephony server apparatus,

wherein the wireless communication gateway server apparatus, the switching apparatus, and the wireless telephony server apparatus communicate through the internet network.

11. A mobile wireless communication system as claimed in claim 2 or 6, comprising:

a satellite network which is connected to the wireless communication gateway server apparatus, the switching apparatus, and the wireless telephony server apparatus,

wherein the wireless communication gateway server apparatus, the switching apparatus, and the wireless telephony server apparatus communicate through the satellite network.

12. A method for mobile wireless communication, comprising the steps of:

storing specification data which represents a specification of a buffer memory of a portable terminal in a buffer memory emulator of a specific wireless communication gateway server apparatus when the portable terminal is connected to the specific wireless communication gateway server apparatus;

changing a specific connection between the portable terminal and the specific wireless communication gateway server apparatus to another connection between the portable terminal and another wireless communication gateway server apparatus, which other apparatus is used when the specific wireless communication gateway server apparatus has a congestion; and,

transferring the specification data from the specific wireless communication gateway server apparatus

to the other wireless communication gateway server apparatus when the other connection is set.

13. A method for mobile wireless communication as claimed in claim 12, comprising the further steps of:

informing a position of the portable terminal from a wireless telephony server apparatus to the specific wireless communication gateway server apparatus; and,

requesting a switching apparatus which sets a connection for the portable terminal based on the informed position to perform a change from the specific connection to the other connection.

14. A method for mobile wireless communication, comprising the step of:

changing a specific connection between the portable terminal and one access point of a wireless communication gateway server apparatus to another connection between the portable terminal and another access point of the wireless communication gateway server apparatus, which other connection is used when the wireless communication gateway server apparatus has congestion.

15. A method of mobile wireless communication as claimed in claim 14, comprising the further steps of:

informing a position of the portable terminal from a wireless telephony server apparatus to the wireless communication gateway server apparatus; and,

requesting a switching apparatus which sets a connection for the portable terminal based on the informed position to perform a change from the specific connection to the other connection.

16. A method for mobile wireless communication as claimed in claim 12 or 14, comprising the further step of:

communicating between the wireless communication gateway server apparatus, the switching apparatus, and the wireless telephony server apparatus through a network.

17. A method for mobile wireless communication as claimed as in claim 12 or 14, comprising the further step of:

communicating between the wireless communication gateway server apparatus, the switching apparatus, and the wireless telephony server apparatus through an internet network.

18. A method for mobile wireless communication as claimed in claim 12 or 14, comprising the further step of:

communicating between the wireless communication gateway server apparatus, the switching apparatus and the wireless telephony server apparatus through a satellite network.

19. A wireless communication gateway server apparatus comprising:

a buffer memory emulator storing specification data which represents a specification of a buffer memory of a portable terminal,

wherein a specific connection with the portable terminal is changed to another connection between the portable terminal and another wireless communication gateway server apparatus, which other apparatus is used when a congestion of the specific connection happens; and,

the specification data in the buffer memory is transferred to other wireless communication gateway server apparatus.

20. A wireless communication gateway server apparatus, as claimed in claim 19,

wherein a request is performed to the switching apparatus which sets a connection for the portable terminal to change from the specific connection to the other connection based on position data of the portable terminal.

21. A wireless communication gateway server apparatus as claimed in claim 19, further comprising:

a plurality of access points, wherein a specific one of the plurality of access points is determined based on an informed position of the portable terminal,

wherein a request is performed to the switching apparatus which sets a connection for the portable terminal to change from a specific connection of the

specific access point to another connection of another access point based on the position of the portable terminal.

22. A mobile wireless communication system substantially as herein described with reference to and as shown in Figures 2 to 9 of the accompanying drawings.

23. A method for mobile wireless communication, the method being substantially as herein described with reference to and as shown in Figures 2 to 9 of the accompanying drawings.

24. A wireless communication gateway server apparatus substantially as herein described with reference to and as shown in Figures 2 to 9 of the accompanying drawings.



INVESTOR IN PEOPLE

Application No: GB 0026358.2
Claims searched: 1-24

Examiner: Robert Macdonald
Date of search: 12 July 2001

Patents Act 1977
Search Report under Section 17

Databases searched:

UK Patent Office collections, including GB, EP, WO & US patent specifications, in:
UK CI (Ed.S): H4L(LDGX, LRAA, LRAB, LED, LECCP, LECCX)
Int CI (Ed.7): H04L(12/66, 29/06); H04Q(7/22, 7/24)
Other: ONLINE: WPI, PAJ, EPODOC, TXTUS0, TXTUS1, TXTUS2, TXTUS3,
TXTGB1, TXTWO1, TXTEP1

Documents considered to be relevant:

Category	Identity of document and relevant passage	Relevant to claims
A,E	GB 2355563 (NEC) See whole document.	

X	Document indicating lack of novelty or inventive step	A	Document indicating technological background and/or state of the art.
Y	Document indicating lack of inventive step if combined with one or more other documents of same category.	P	Document published on or after the declared priority date but before the filing date of this invention.
&	Member of the same patent family	E	Patent document published on or after, but with priority date earlier than, the filing date of this application.

This Page Blank (uspto)